



ENVIRAL® Oberflächenveredelung GmbH · Altdorfer Weg 6 · D-14823 Niemege

Wir danken für Ihr Vertrauen!

Altdorfer Weg 6 | info@enviral.de
D-14823 Niemege | www.enviral.de

Telefon +49 (0) 33843 642-04
Telefax +49 (0) 33843 642-24

kostenlose Servicenummer
0-800/ENVIRAL 0-800/368 47 25

All technical recommendations for application we give to our clients to the best of our knowledge and according to the state of the art are not binding. According to our General Terms and Conditions of Business they do not establish any contractual legal relationship and no ancillary obligations resulting from the purchase contract. This does not release the client from his/her own responsibility to check our services, products and recommendations with regard to their suitability for the intended use. Our General Terms and Conditions of Business apply, which you can view at any time at www.enviral.eu.

DATA SHEET

ENV 203 – Powder coating

Substrate material:

STEEL and STAINLESS STEEL

Component measurements:

up to l = 13,600 x w = 2,500 x h = 4,000 mm
up to l = 17,500 x w = 1,000 x h = 2,000 mm
Exterior application

Component weight:

up to 3,000 kg

Process:

Blasting, ENVIRAL curing primer and powder coating

Product description:

Surface pre-treatment and surface coating on a lead-, chromium-, cadmium- and solvent-free basis in facade quality

Properties:

The powder coating is tested and approved by the "Gütegemeinschaft für Stückgutbeschichtung".

- Highest weather resistance
- Best mechanical properties
- Good flow
- Chromium-, lead-, cadmium- and solvent-free

Application:

Coating of profiles, sheets and constructions made of steel and stainless steel for exterior application

Process restrictions:

Cavities, sharp edges and concealed areas (e.g. doublings) cannot be protected. These restrictions only apply to steel components, not to stainless steel.

03 / 2022

ENV 203 / page 1

Geschäftsführer Ing. Rainer Rogovits
Amtsgericht Potsdam HRB 7819
Ust.-IdNr. DE 166554396
St.-Nr. 048/108/03245

Bankverbindungen Berliner Sparkasse · BIC BELADEBEXX
IBAN DE79 1005 0000 6610 0036 86
VR-Bank Fläming eG · BIC GENODEF1LUK
IBAN DE37 1606 2008 4105 6930 00



When producing the parts, it is necessary to ensure that machining fluids and greases are removed - especially around non-visible areas, unavoidable doublings, blind holes, threads, etc. - as these cannot be completely cleaned off by the blasting process and therefore have a negative effect on the powder coating layer and durability during the curing process.

- Color tones:**
- Approx. 180 RAL colors (smooth glossy, smooth satin finish, smooth matt, (coarse) textured glossy)
 - Standard RAL colors also available as ENV Antimicrobial
 - Metallic, approx. P-tones, approx. DB metallic
 - Pearlescent mica metallic
 - Special color tones NCS; Sikkens or according to color samples
 - Effect powder coatings: ENVnatuRAL Design, ENVTransparent, etc.
- Process description:**
- Blasting (compare data sheet ENV 700)
 - Dust removal
 - Priming with ENVIRAL curing primer
 - Curing
 - Powder coating
 - Curing
- Notes:** **Residues of blasting media in component cavities are to be expected! These cannot be completely removed. - Please take this into account when further processing and completing your components (e.g. protection of mechanical/movable built-in parts).**
- Assessment of the surface:**
- The finished coated surface is assessed in accordance with the Association of Window and Facade Manufacturers (Verband der Fenster- und Fassadenhersteller e.V.), VFF leaflet ST.02, status August 2016 (Visual assessment of organically coated surfaces on steel) and delivered in this quality. Additional requirements, including standard requirements or requirements of service specifications, are only valid if they have been explicitly confirmed in writing by ENVIRAL®.
- Suspension:** According to our suspension recommendations (compare data sheet ENV 800)
- Quality assurance:** Continuing process control and order-specific quality assurance, destructive and non-destructive
- Packaging:** Noppa foam, air cushion film
- Repair:** According to our repair recommendations (compare data sheet ENV 802)
- Cleaning:** According to our cleaning recommendations (compare data sheet ENV 801)

Sealant adhesion: According to sealant adhesion on powder-coated surfaces of facades (compare data sheet ENV 803)

Approvals: Environmental Product Declaration according to ISO 14025 and EN 15804:
EPD-VDL-20160263-IAG1-EN: Polyester powder coating
EPD-VDL-20160264-IAG1-EN: Epoxy powder coating
EPD-VDL-20160265-IAG1-EN: Hybrid powder coating
EPD-GDA-20190070-IBH1-EN: Aluminum profile coated