



ENVIRAL® Oberflächenveredelung GmbH · Altdorfer Weg 6 · D-14823 Niemege



Oberflächenveredelung GmbH

Wir danken für Ihr Vertrauen!

Altdorfer Weg 6 | info@enviral.de
D-14823 Niemege | www.enviral.de

Telefon +49 (0) 33843 642-04
Telefax +49 (0) 33843 642-24

kostenlose Servicenummer
0-800/ENVIRAL 0-800/368 47 25

All technical recommendations for application we give to our clients to the best of our knowledge and according to the state of the art are not binding. According to our General Terms and Conditions of Business they do not establish any contractual legal relationship and no ancillary obligations resulting from the purchase contract. This does not release the client from his/her own responsibility to check our services, products and recommendations with regard to their suitability for the intended use. Our General Terms and Conditions of Business apply, which you can view at any time at www.enviral.eu.

DATA SHEET

ENV 700 – Blasting

Substrate material:

ALUMINUM, STEEL, STAINLESS STEEL, STEEL galvanized

Component measurements:

- a) l = 13,600 x w = 2,500 x h = 4,000 mm, up to 3,000 kg or
l = 17,500 x w = 1,000 x h = 2,000 mm, up to 3,000 kg (for stainless steel with separate agreement)
- b) l = 17,500 x w = 1,000 x h = 2,000 mm, up to 3,000 kg
- c) l = 7,000 x w = 2,300 x h = 3,300 mm, up to 1,000 kg

Process:

Blasting, Sweeping/fine blasting or glass bead blasting

Product description:

Mechanical surface pre-treatment as preparation for powder coating, water-based coating, painting or galvanizing as well as finished surface (e.g. glass bead blasting of stainless steel).

Notes:

Residues of blasting media in component cavities are to be expected! These cannot be completely removed. - Please take this into account when further processing and completing your components (e.g. protection of mechanical/movable built-in parts).

Mechanical distortion is to be expected with thin-walled parts.

Blasting media:

- a) Iron-free regular corundum (or for stainless steel with glass beads)
- b) Steel shot
- c) Glass beads

03 / 2022

ENV 700 / page 1

Geschäftsführer Ing. Rainer Rogovits
Amtsgericht Potsdam HRB 7819
Ust.-IdNr. DE 166554396
St.-Nr. 048/108/03245

Bankverbindungen Berliner Sparkasse · BIC BELADEVXXX
IBAN DE79 1005 0000 6610 0036 86
VR-Bank Fläming eG · BIC GENODEF1LUK
IBAN DE37 1606 2008 4105 6930 00



Application:

- Paint stripping and rust removal
- scale removal
- Mechanical pre-treatment of constructions made of aluminium steel, galvanized steel and stainless steel that cannot be wet-chemically pre-treated (sweeping)
- Finished surface (stainless steel)

Process description:

a) Pressure blasting system I:

- up to l = 13,600 x w = 2,500 x h = 4,000 mm, up to 3,000 kg
- for components made of aluminum, steel, galvanized steel, stainless steel
- with separate agreement stainless steel can also be blasted with glass beads as follows:
up to l = 17,500 x w = 1,000 x h = 2,000 mm, up to 3,000 kg
- iron-free regular corundum
- flexible machining by hand
- compressed air blast media mixture is applied to the parts by a pressure jet blower and produces abrasion
- fine blasting / sweeping possible (pressure variably adjustable 2 to 6 bar)
- blasting medium runs over magnetic separator

b) Wheel blast system:

- up to l = 17,500 x w = 1,000 x h = 2,000mm, up to 3,000kg
- for steel components (smooth beams, tubes, etc.)
- steel shot
- automatic machining
- steel shot is accelerated to high speed by centrifugal wheels, thus applied to the parts, producing economic abrasion

c) Pressure blasting system II:

- up to l = 7,000 x w = 2,300 x h = 3,300mm, up to 1,000kg
- for components made of aluminum, stainless steel, glass
- glass beads
- attaining matte, satinized, visually very appealing surfaces on aluminum and stainless steel as well as matte surfaces on glass
- Note for parts made of aluminum and stainless steel: slight damage and tarnishing, e.g. caused by welding of the parts, cannot be removed by glass bead blasting

Quality assurance:

Visual inspections and, upon request, surface roughness measurement and documentation